




MODEL H2881 4" PNEUMATIC DRUM SANDER INSTRUCTION SHEET

⚠ WARNING



EYE/EAR INJURY HAZARD!
Wear safety glasses and hearing protection during use of this tool!



OVER INFLATION HAZARD!
Never exceed 8 PSI!



RESPIRATORY HAZARD!
Sanding produces fine dust. Wear the appropriate protection during use!

Introduction

This rolling-pin style pneumatic drum sander is perfect for hand contouring and smoothing projects that are too large to use with a stationary sander. Simply chuck the $\frac{3}{8}$ " spindle into a portable electric drill, cordless drill or air powered drill for two-handed control. Choose this 4" x $1\frac{1}{8}$ " diameter size for getting into tight areas. Features ball bearing handle and air valve for easy bicycle pump inflation.

Inventory

- A. Drum Sander..... 1
- B. Spare Valve Cap..... 1

Operation

Slide the sanding sleeve over the drum. Remove the plastic cap on the handle with a small screw driver to expose the air valve. Inflate to the desired pressure. DO NOT exceed 8 PSI!



Figure 1. Model H2881.



Figure 2. Pneumatic drum sander in action.

4" Aluminum Oxide Sanding Sleeves

- H3875** $1\frac{1}{8}$ " x 4" x 60 Grit
- H3876** $1\frac{1}{8}$ " x 4" x 100 Grit
- H3877** $1\frac{1}{8}$ " x 4" x 150 Grit
- H3878** $1\frac{1}{8}$ " x 4" x 180 Grit
- H3879** $1\frac{1}{8}$ " x 4" x 220 Grit
- H3880** $1\frac{1}{8}$ " x 4" x 320 Grit

If you need help with your new pneumatic tool, call our Tech Support at: (570) 546-9663.

COPYRIGHT © MARCH, 2006 BY GRIZZLY INDUSTRIAL, INC.

WARNING: NO PORTION OF THIS MANUAL MAY BE REPRODUCED IN ANY SHAPE OR FORM WITHOUT THE WRITTEN APPROVAL OF GRIZZLY INDUSTRIAL, INC.

#PC8119 PRINTED IN TAIWAN